



ANTI-SLIP DECKING OIL

Slip-resistant top coat for exterior use!



430 Clear Satin



1 COAT

Product description:

Clear, satin top coat for decking already treated with coloured oil. Contains a specialized highly compressed organic non-slip additive, which is evenly distributed in the coating and reduces slips when dry. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Easy and seamless application. Finish stays workable while coating. Water-repellent natural oil based surface will not crack, peel, flake or blister. No sanding necessary, just simply recoat. Osmo Anti-Slip Decking Oil contains active ingredients to protect the coating against mould, algae and fungal attack.

Recommended use:

Osmo Anti-Slip Decking Oil is especially suited for all timber decking and stairs in outdoor areas made of e.g. Bangkirai, Massaranduba, Garapa, Larch, Douglas Fir or Pine. Suitable for ribbed, grooved and particularly for smooth decking surfaces.

Ingredients:

Based on natural plant oils (sunflower oil, soybean oil, thistle oil and linseed oil), siccatives (drying agents) and additives. Biocidal active ingredient: Propiconazole. Dearomatized white spirit (benzene-free). EU limit value for this product (cat. A/i): 500 g/l VOC (2010). This product contains max. 500 g/l VOC. Detailed declaration of ingredients available upon request.

Technical Data:

Specific gravity: 0.9-1.0 g/cm³
 Viscosity: 20-25s DIN 53211/4 mm, viscous
 Odour: faint/mild, odourless after drying
 Flashpoint: > 63 °C, acc. DIN EN ISO 2719
 pH value: not required

Storage:

5 years and longer if stored in the closed original can. If thickened by frost, store at room temperature for 24 hours prior to use.

Surface Preparation:

We recommend a base coat with a pigmented oil, such as Osmo Bangkirai-Oil, Larch-Oil or Douglas Fir Oil or Osmo Natural Oil Woodstain. Osmo Anti-Slip Decking Oil protects against weathering and extends the life of the coating. For renovation works, clean old microporous finishes thoroughly. Degrey and clean already greyed or weathered wood at the same time with Osmo Wood Reviver Power-Gel. Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Anti-Slip Decking Oil is ready to use. Do not thin. Stir well before use. Old paints, varnishes and lacquers must be completely removed. Always wear a dust mask while sanding. If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:

With Osmo Flat Brush, apply thinly along the wood grain and spread well. For quicker application on larger areas, we recommend our Osmo Decking Brush (150 mm) which is tailored for decking and allows you to work ergonomically. Spread well and evenly. Allow to dry for approx. 12 hours under good ventilation. For renovation works, one coat applied to the clean and dry surface is usually sufficient.



Cleaning of tools:

With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:

Approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Coverage:

Product coverage for 1 coat is 24 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:

Osmo Anti-Slip Decking Oil is clear, and therefore, it offers only limited protection against UV radiation (greying). With a combination of a coloured base coat and a top coat with Osmo Anti-Slip Decking Oil, your decking is fully protected. Anti-Slip Decking Oil is not suitable for a single product application. Oils enhance the natural colour tone of wood (permanent wet effect). To avoid greying and declining non-slip effect on high-traffic areas, these areas should be recoated at the right time. If the greying process has already begun, degrey the surface with Osmo Wood Reviver Power Gel and recoat. Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

Caution:

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Contains propiconazole (ISO). May cause an allergic reaction. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Harmful to aquatic life with long lasting effects. Avoid release to the environment. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

Disposal:

Dispose of product residuals and completely emptied containers according to the local official guidelines (EU-waste code key number 08 01 11*). Only fully emptied containers can be recycled.

Colour tone:

430 Clear Satin

Size:

0.75 l; 2.5 l; 25 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 09/20