



## WOOD REVIVER

### POWER-GEL

Highly effective cleaning and refreshing of greyed wood!



6609 Clear



1 APPLICATION

#### Product description:

Cleaner for refreshing and cleaning greyed wood in outdoor areas. Wood Reviver Power-Gel is a non-drip product, and thus it is easy to apply – especially on vertical surfaces. The gel penetrates the wood deeply and removes grey patina, and afterwards by re-oiling, the fresh warm colour tone of the wood is restored.

#### Recommended use:

Osmo Wood Reviver Power-Gel is highly recommended for timber decking, cladding, garden furniture and similar surfaces.

#### Ingredients:

Osmo Wood Reviver Power-Gel contains biodegradable oxalic acid

#### Technical Data:

Specific gravity: 0.99-1.05 g/cm<sup>3</sup>

Viscosity: >70s DIN EN ISO 2431/3 mm, thixotropic

Odour: faint/mild, odourless after drying

Flashpoint: not required

pH value: >2,1

#### Storage:

2 years and longer if stored in the closed original can.  
Do not expose to frost or temperatures above 30 °C!

#### Surface Preparation:

Remove debris from greyed wood; afterwards dampen with water. Wood Reviver Power-Gel is ready to use. Do not thin. Perform a trial application before treating wood with Wood Reviver Power-Gel.

#### Methods of Application:

Generously apply the gel along the wood grain. After approx. 20 minutes reaction time, clean surface with Osmo Decking Cleaning Brush and rinse with a lot of water. After drying for approx. 48 hours, protect the newly refreshed wood with a wood finish (e.g. Osmo Natural Oil Woodstain, Decking-Oils, Country Colour). For machine processing on decking, we recommend using Osmo Decking and Flooring Cleaner.

#### Cleaning of tools:

With soap and water.

#### Drying time:

Allow wood to dry thoroughly (approx. 24-48 hours) before applying a new surface coating. Lower temperatures and/or higher air humidity may increase drying times.

#### Coverage:

1 litre covers approx. 10 m<sup>2</sup> with one application. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

#### Note:

Protect metal (e.g. hinges) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.)



**Caution:**

Keep out of reach of children. Contains mixture of: 5-chloro-2-methyl-2 H-isothiazol-3-one (CMIT) and 2-methyl-2 H-isothiazol-3-one (MIT) (3:1). May cause an allergic reaction. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Safety data sheet available on request. Note: Protect metal (e.g. hinges) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.)

**Colour tone:**

6609 Clear

**Size:**

0.5 l; 2.5 l; 5.0 l; 10 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 03/21

**Disposal:**

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 07 06 99). Only completely emptied cans can be recycled.